

## CLAIMS

1. A method of operation for a vehicle braking system including a driver activated brake pedal, a brake pressure modulator, and an anti-lock brake control that activates the brake pressure modulator to modulate vehicle braking upon detection of an insipient wheel lock condition, the method
- 5 comprising the steps of:

periodically measuring vehicle deceleration and a brake pedal position during activation of the braking system when said insipient wheel lock condition is not detected;

- identifying conditions of degraded braking effectiveness based on
- 10 the periodically measured deceleration and brake pedal position; and
- adaptively adjusting a brake pressure control parameter of said anti-lock brake control when a condition of degraded braking effectiveness is identified so as to compensate for the identified condition.

2. The method of Claim 1, wherein the anti-lock brake control releases and then re-applies brake pressure at a determined apply rate upon detection of an insipient wheel lock condition, and the step of adaptively
- 5 adjusting a brake control parameter includes adjusting the determined apply rate in a manner to provide an increased rate of brake pressure application.

3. The method of Claim 1, wherein the identified condition of degraded braking effectiveness is brake wear, and the determined apply rate is increased by a predefined factor.

4. The method of Claim 1, wherein the anti-lock brake control releases and then re-applies brake pressure at a determined apply rate upon detection of an insipient wheel lock condition, the method including the steps of:

- 5           estimating a road surface coefficient of friction based on the  
periodically measured deceleration and brake pedal position;  
             determining said apply rate based on the estimated road  
coefficient of friction when conditions of degraded braking effectiveness are  
not identified; and
- 10           determining said apply rate based on the estimated road  
coefficient of friction and a measure of braking effectiveness degradation  
when the condition of degraded braking effectiveness is identified.

5. The method of Claim 4, wherein the step of determining the  
apply rate when the condition of degraded braking effectiveness is identified  
includes the steps of:

- 5           compensating the estimated road surface coefficient of friction for  
error due to the identified condition of degraded braking effectiveness; and  
             determining the apply rate based on the compensated estimate of  
road surface coefficient of friction and the measure of braking effectiveness  
degradation.

6. The method of Claim 4, wherein the identified condition of  
degraded braking effectiveness is brake fading, and the measure of braking  
effectiveness degradation is determined according to an amount by which an  
estimate of brake temperature exceeds a nominal brake temperature.

7. The method of Claim 4, wherein the identified condition of  
degraded braking effectiveness is fluid leakage, and the measure of braking  
effectiveness degradation is determined according to an estimated rate of the  
fluid leakage.

8. The method of Claim 4, wherein the braking system includes  
an adjustable brake, the identified condition of degraded braking

- effectiveness is mis-adjustment of said adjustable brake, and the measure of braking effectiveness degradation is determined according to a difference in
- 5 wheel speeds attributable to such mis-adjustment.

9. The method of Claim 4, wherein the identified condition of degraded braking effectiveness is excessive vehicle weight, and the measure of braking effectiveness degradation is determined according to an amount by which an estimate of vehicle weight exceeds a reference weight.

2025 RELEASE UNDER E.O. 14176